

## S-500® CF Coolant Concentrate: Water Soluble Oil

### FEATURES

- Chlorine Free Extreme Pressure Technology
- Excellent Sump Life
- General Purpose
- Long Lasting And Bio-Stable
- Maximizes Tool Life
- Non-Hazardous
- Non-Irritating
- Non-Toxic

**Approved by Airbus, American Airlines, Boeing, Bombardier, Lockheed-Martin, Lord, Messier-Bugatti-Dowty, Pratt & Whitney, United Technologies, and Rolls Royce**

### GENERAL DESCRIPTION

The first choice for general machining for all metals and non-traditional materials. The EP properties produce excellent results over a broad range of manufacturing conditions. This general purpose product satisfies some of the most demanding manufacturing operations from stamping, milling and turning processes. Amine free and safe on all materials while providing the best finishes and tool life on aluminum, steel to stainless steel.

### APPLICATIONS

Primary		Secondary	
Blanchard	Reaming	Burnishing	Forming
Drilling	Stamping	Broaching	Surface Grinding
Milling	Turning	Creep Feed Grinding	

### MATERIALS

Primary		Secondary	
Aluminum	Plastics	Brass	Glass
Chromium Alloys	Powdered Metals	Bronze	Graphite
High Temp Alloys	Precious Metals	Ceramics	Refractory Metals
Molybdenum	Steel	Copper	Stainless Steel
Nickel Alloys	Titanium		

### INSTRUCTIONS

Always premix coolant before adding to the machine sump. When mixing coolant by hand it is important to always add the concentrate to the water and then agitate. For best results, a Hangsterfer's recommended proportioning unit should be used. To maintain recommended concentration, make-up should be added at one-half the desired concentration. Always check concentration with a Refractometer. To maintain 6%: first charge the machine at 6%, then, as needed, add make-up as much as 3%. Avoid adding straight water or concentrate directly to the machine.

OPERATION	CONCENTRATION		
	%	Ratio Concentrate: Water	Refractometer
General Grinding	5	1:20	5
General Machining and Turning	7.5	1:13	7.5
Grinding with aggressive feed rates	10	1:10	10
Drilling, Tapping, Reaming	10	1:10	10
Light Stamping and Forming	10	1:10	10

## MAINTENANCE

S-500 CF is a bio-stable coolant, designed to control the growth of bacteria. Regular maintenance is required for maximum performance. Concentration should be monitored regular with a calibrated refractometer. S-500 CF gives a direct read on the refractometer (E.G. 5=5%).

## PRODUCT CHARACTERISTICS

Product: S-500 CF		Concentration Dilution Table		
Form	Liquid			
Color	Green			
Odor	Mild			
Specific Gravity	0.93	%	<i>Ratio</i> Concentrate: Water	Refractometer
Viscosity: SUS @ 100°F	<b>200</b>	20%	1:5	20
cSt @ 40°C	<b>43</b>	15%	1:7	15
Flash Point, COC, °F/°C	325/162	10%	1:10	10
Fire Point, COC, °F/°C	345/173	7.5%	1:13	7.5
Pour Point, °F/°C	<0/-18	5%	1:20	5
Solubility in Water	100%	4%	1:25	4
Boiling Point, °F/°C	289/143	3%	1:33	3
Vapor Pressure, mm Hg @ 25°	<0.01	2.5%	1:40	2.5
pH @ 10%	9.1	2%	1:50	2
Chlorine	0%	1%	1:10	1

Refractive Index Multiplier = 1

## WASTE TREATMENT

Dispose of in accordance with local, state, federal and international laws. If and when it is necessary to dispose of waste fluids, the amount of waste can be greatly reduced by separating the water from the oil and contaminants which accumulate through normal machining. You can often reduce your waste disposal by more than 80% through conventional methods such as Ultra-Filtration, Chemical Treatment or Evaporation. After approval by your local, state, or federal authorities, the waste water may sent to the sewer or discharged into waters, and the separated oils may be removed for recycling, sale or disposal.

## SHIPPING UNITS

All Hangsterfer's products are available in pails, drums and Intermediate Bulk Containers (275 or 330 gallons). All products are distributed worldwide.

Date: 11/5/08 Revised: 1/21/16

Disclaimer: All reasonable care has been taken to ensure that the information contained in this publication is true and accurate. No warranty is expressed or implied regarding the accuracy of the data. The general description, recommended uses, application data and statements in the product literature are guidelines. Because this product may be used for a variety of applications over which Hangsterfer's Laboratories, Inc. has no control, Hangsterfer's Laboratories, Inc. assumes no liability for incidental, consequential, or direct damages of any kind, regardless of causes, including negligence. Also, seller is not liable for any loss, damage or liability resulting from the use of the product in the buyer's manufacturing processes or in combination with other substances. SDS's are available for all Hangsterfer's products and should be consulted as needed.

